

## 8026 Color Laser Printer

Meet the demands of the busy office with the Intelliprint 8026.



- Fast 26 ppm color, 36 ppm mono
- PCL5C/6 and Adobe PostScript Standard
- Robust monthly workload up to 100,000 pages/month
- Ethernet USB2 and Parallel standard
- Intellifilter forms management
- 1200 dpi for quality business documents
- Duplex standard
- Prints on a variety of media

### **Meet the demands of the busy office**

The Intelliprint 8026 color laser printer delivers 26 ppm in full color and 36 ppm in black and white, increasing the efficiency in your work place. TallyGenicom's Intelliprint technology ensures professional high quality color output, text graphics, reports, presentations even photographs all in bright vibrant colors.

### **Intelligent Forms**

Like all Intelliprint printers, legacy data is no problem; Intellifilter resident within the Intelliprint 8026 enables true migration from other technologies such as Line printer or SIDM (Serial Dot Matrix). All this without expensive server software changes.

### **Is Security an issue?**

Add compact flash or a micro drive and secure printing is enabled. Just add a PIN code in the printer and collect your output. In addition Job Accounting, Job Library, Collation and the ability to store forms, fonts and logos etc. become possible.

|                              |  |
|------------------------------|--|
| <b>Print Speed</b>           | 26 ppm color; 36 ppm monochrome  |
| <b>Print Method</b>          | Single pass electrophotographic laser  |
| <b>Processor</b>             | MIPS R7000 533 Mhz   |
| <b>Resolution</b>            | 1200 x 1200 dpi  |
| <b>Time To 1st Page</b>      | 8 seconds  |
| <b>Memory</b>                | 128MB Standard; Maximum 256MB, 1 slot  |
| <b>Standard Connectivity</b> | USB 2, Ethernet TCP/IP, (10BaseT/ 100BaseT), IEEE Parallel   |
| <b>Standard Emulation</b>    | PCL5C, PCL6, Adobe PostScript 3  |
| <b>Print Monitor</b>         | Built in Web Server  |
| <b>Fonts</b>                 | 86 PCL Fonts, 135 Postscript Fonts   |
| <b>Consumables</b>           | CMY=8,000 images each; K=9,000 images (@ 5% coverage on A4) (starter toner 4.5k black; 4K CMY)   |
| <b>STD Paper Handling</b>    | 150 sheet multipurpose feeder; 550 sheet tray  |
| <b>Opt'l Paper Handling</b>  | 1 x 550 sheet feeder or 2 x 550 sheet feeder   |
| <b>Paper Type</b>            | Plain paper, Heavy paper, Transparencies, Labels, Postcards, Coated and Envelopes  |
| <b>Paper Size</b>            | A5, B5, A4, Executive, Letter, Legal, Oficio, A6 from tray 1 (MPF); Custom sizes up to 8.5" X 35.4" tray 1                               |
| <b>Paper Output</b>          | Output capacity 250 sheets face down   |
| <b>Printable Area</b>        | 4 mm unprintable edge  |
| <b>Physical Weight</b>       | Intelliprint 8026DN - 34.5 Kg/76lbs including consumables; Intelliprint 8026DNT - 56 Kg/123.2lbs including consumables                   |
| <b>PhysicalSize</b>          | Intelliprint 8026 DN - 429mm x 580mm x 457mm, 16.9" x 22.8" x 18"  |
| <b>Power Voltage</b>         | EMEA: 220-240V ±10%; US: 110 - 127V ±10%, 11.8 amps @110v.   |
| <b>Power Frequency</b>       | 50/60 Hz   |
| <b>Power Consumption</b>     | 45 Watts in Sleep mode (fuser off), 200 Watts in Standby (fuser on)580 Watts average operation, 1,300 Watts maximum                      |
| <b>Compliance</b>            | ENERGY STAR® Qualified, cULus Listed 60950, FCC Part 15 Class B, ICES-003, FDA reg21 CFR Chapter 1 Subchapter J 1002.10 and 1002.12, NOM |
| <b>Workload</b>              | Up to 90,000 images per month maximum  |
| <b>Reliability MTBF</b>      | 100,000 images   |
| <b>Forms Software</b>        | TG Forms   |
| <b>Drivers</b>               | Windows - 98, ME, NT4, 2000, XP; Server 2003 32/64 bit, Vista 32/64 bit; MAC OS 10.2 or later; Linux CUPS                                |
| <b>Temperature</b>           | 5° - 32° C; 41°F to 90°F   |
| <b>Humidity</b>              | 15% - 85% relative humidity, non-condensing  |
| <b>Acoustic</b>              | Operating - less than 55 dB(A); Standby - less than 35 dB(A); Sleep - background   |
| <b>Warranty</b>              | One year on-site   |
| <b>Option 1</b>              | 1 x 550 sheet feeder; 2 x 550 sheet feeder   |
| <b>Option 2</b>              | Memory exp. 256MB  |
| <b>Option 3</b>              | 4GB Microdrive   |



Tally and TallyGenicom are registered trademarks of TallyGenicom, L.P. All other company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice. Copyright © 2008 TallyGenicom, L.P.

Printed Date: 07/01/2008



4500 Daly Drive, Suite 100  
 Chantilly, VA 20151  
 T 800.436.4266  
 www.tallygenicom.com